

SHELL SIZE	A THREAD	B MAX	C MAX	D MAX	E MAX	F MAX
12	5/8 -24UNEF	21,7	14,7	26,2	22,2	26,2
14	3/4 -20UNEF	24,8	15,3	27,1	25,4	27,7
16	7/8 -20UNEF	28,8	16,0	27,0	28,6	29,2
18	1 -20UNEF	32,0	16,7	27,4	30,1	31,2
20	1 1/8 -18UNEF	35,0	17,7	29,1	33,2	33,7
22	1 1/4 -18UNEF	38,3	18,1	29,4	38,0	32,7
24	1 3/8 -18UNEF	41,5	18,6	30,5	39,6	34,7
28	1 5/8 -18UNEF	48,0	20,1	31,1	41,4	41,7
32	1 7/8 -16UNEF	54,5	21,1	32,0	41,4	44,2


ENTRY SIZE	G	H MAX
03	4,77	16,8
04	6,35	18,8
05	7,92	20,4
06	9,52	22,0
07	11,12	23,5
08	12,70	25,0
09	14,27	26,7
10	15,88	28,3
11	17,47	30,0
12	19,05	31,5
13	20,62	33,0
14	22,23	34,7
15	23,82	36,4
16	25,40	37,8
18	28,57	39,4
20	31,80	44,2
22	34,90	47,3
24	38,10	50,9

NOTE:  
NON-STANDARD LENGTHS AVAILABLE FOR  
STRAIGHT ADAPTORS ONLY. PLEASE  
CONSULT FACTORY

NOTE:  
FOR ENVIRONMENTAL SEALING  
PLEASE USE GROMMET SB-\*\*\*-\*\*G  
(SUPPLIED BY AB CONNECTORS)

77R1-18-08-1-C

SERIES \_\_\_\_\_  
CONNECTOR INTERFACE \_\_\_\_\_  
ANGLE \_\_\_\_\_  
SHELL SIZE \_\_\_\_\_  
ENTRY SIZE \_\_\_\_\_  
MATERIAL \_\_\_\_\_  
PLATING \_\_\_\_\_

STRAIN RELIEF ADAPTOR	SERIES 77 TO FIT CONNECTOR CODE R
	THIS DRAWING IS THE COPYRIGHT AND THE PROPERTY OF POLAMCO LTD. IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT WRITTEN CONSENT OF THE COMPANY
 <b>POLAMCO LTD</b>	
WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP	