



SHELL SIZE	A THREAD	B MAX	C MAX	D MAX	E MAX
08	$\frac{7}{16}$ -28UNEF	17,3	21,5	28,0	7,1
10	$\frac{9}{16}$ -24UNEF	20,3	21,5	30,0	10,5
12	$\frac{11}{16}$ -24UNEF	23,8	23,5	31,0	13,4
14	$\frac{13}{16}$ -20UNEF	26,8	23,5	33,0	16,5
16	$\frac{15}{16}$ -20UNEF	29,8	24,5	34,4	19,7
18	$1\frac{1}{16}$ -18UNEF	33,3	27,5	36,0	22,2
20	$1\frac{3}{16}$ -18UNEF	36,3	34,5	37,6	25,6
22	$1\frac{5}{16}$ -18UNEF	39,8	34,5	39,5	28,5
24	$1\frac{7}{16}$ -18UNEF	42,8	34,5	42,0	31,7

96F1-16-1-B

SERIES _____
CONNECTOR INTERFACE _____
ANGLE _____
SHELL SIZE _____
MATERIAL _____
PLATING _____

STRAIN RELIEF ADAPTOR	SERIES 96 TO FIT CONNECTOR CODE F
	THIS DRAWING IS THE COPYRIGHT AND THE PROPERTY OF POLAMCO LTD. IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT WRITTEN CONSENT OF THE COMPANY
POLAMCO LTD	WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP