



SHELL SIZE	A THREAD	B MAX	C MAX	D MAX	E MAX	F MAX	J - 10 K MAX	J - 15 K MAX	J - 20 K MAX	J - 25 K MAX	J - 30 K MAX	J - 35 K MAX	J - 40 K MAX	J - 45 K MAX	J - 50 K MAX
09	M12 x 1.0	20,0	13,1	24,7	27,7	30,4	29,4	34,4	39,4	44,4	49,4	54,4	59,4	64,4	69,4
11	M15 x 1.0	23,0	13,9	25,9	31,2	32,2	30,3	35,3	40,3	45,3	50,3	55,3	60,3	65,3	70,3
13	M18 x 1.0	26,5	14,5	26,3	34,2	33,7	31,1	36,1	41,1	46,1	51,1	56,1	61,1	66,1	71,1
15	M22 x 1.0	31,0	15,5	27,2	37,2	35,2	32,0	37,0	42,0	47,0	52,0	57,0	62,0	67,0	72,0
17	M25 x 1.0	34,5	16,1	28,0	40,7	36,9	33,0	38,0	43,0	48,0	53,0	58,0	63,0	68,0	73,0
19	M28 x 1.0	37,5	16,8	28,3	44,7	38,5	33,8	38,8	43,8	48,8	53,8	58,8	63,8	68,8	73,8
21	M31 x 1.0	39,0	17,1	29,1	47,2	40,1	34,7	39,7	44,7	49,7	54,7	59,7	64,7	69,7	74,7
23	M34 x 1.0	42,0	17,7	29,5	50,2	41,6	35,7	40,7	45,7	50,7	55,7	60,7	65,7	70,7	75,7
25	M37 x 1.0	45,5	18,4	30,4	53,2	43,1	36,7	41,7	46,7	51,7	56,7	61,7	66,7	71,7	76,7

ENTRY SIZE	G	H MAX
08	6,4	14,0
10	7,9	15,5
12	9,5	17,1
14	11,1	18,7
16	12,7	20,3
20	15,9	23,5
24	19,0	26,7
28	22,2	29,8
32	25,4	33,0
36	28,6	36,2
40	31,8	39,4

**APH1-17-16-25-1-B(-A86)**

SERIES  
CONNECTOR INTERFACE  
ANGLE (1 - STRAIGHT)  
(2 - 45°)  
(3 - 90°)  
SHELL SIZE  
ENTRY SIZE  
CHAMBER LENGTH J (STRAIGHT ONLY)  
MATERIAL (1 - ALUM ALLOY)  
(2 - ALUM BRONZE)  
FINISH (B - CAD OLIVE OVER NICKEL)  
(C - ELECTROLESS NICKEL)  
(Z - NON-REFLECTIVE SHOT BLAST)  
NON-MAGNETIC OPTION (OMIT FOR STANDARD)

BANDING ADAPTOR	<b>SERIES AP</b>
	TO FIT MIL-DTL-38999 SERIES III & IV
THIS DRAWING IS THE COPYRIGHT AND THE PROPERTY OF POLAMCO LTD. IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT WRITTEN CONSENT OF THE COMPANY	
 <b>POLAMCO LTD</b> WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP	