



SHELL SIZE	A THREAD	B MAX	E MAX	F MAX
09	M12 x 1.0	18,0	22,0	28,5
11	M15 x 1.0	21,0	25,5	30,2
13	M18 x 1.0	24,5	28,4	31,7
15	M22 x 1.0	27,5	32,4	33,2
17	M25 x 1.0	31,0	35,7	34,9
19	M28 x 1.0	34,0	38,9	36,5
21	M31 x 1.0	37,0	41,2	38,1
23	M34 x 1.0	40,0	44,2	38,6
25	M37 x 1.0	43,5	47,2	41,1

ENTRY SIZE	G	H LENGTH	CABLE RANGE
05	7,92	40	4,5 - 9,0
08	12,70	40	6,0 - 12,0
10	15,88	48	7,5 - 15,0
12	19,05	48	9,0 - 18,0
16	25,40	55	10,0 - 25,0
20	31,80	70	12,5 - 25,0
24	38,10	70	15,0 - 36,0

CONDUCTIVE ADHESIVE

HOT-MELT ADHESIVE

TAKSH3-17-12-2-Z-SB

SERIES
CONNECTOR INTERFACE
ANGLE (3 - 90°)
SHELL SIZE
ENTRY SIZE
MATERIAL (MARINE BRONZE)
SHOT BLAST FINISH
SCREENED BOOT HEAT SHRINK TERMINATION

POLAMCO PART NUMBER	NATO STOCK NUMBER
TAKSH3-09-05-2-Z-SB	5935-99-387-2255
TAKSH3-11-08-2-Z-SB	5935-99-343-1528
TAKSH3-13-10-2-Z-SB	5935-99-402-7144
TAKSH3-15-12-2-Z-SB	5935-99-990-0320
TAKSH3-17-12-2-Z-SB	5935-99-986-6684
TAKSH3-19-12-2-Z-SB	5935-99-846-4580
TAKSH3-21-16-2-Z-SB	5935-99-724-3709
TAKSH3-23-16-2-Z-SB	5935-99-873-6328
TAKSH3-25-24-2-Z-SB	5935-99-499-9689

HEAT SHRINK ADAPTOR	TAKSH3 SB
	TO FIT CONNECTOR MIL-C-38999 SERIES III CECC SPEC. THIS DRAWING IS THE COPYRIGHT AND THE PROPERTY OF POLAMCO LTD. IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT WRITTEN CONSENT OF THE COMPANY
	POLAMCO LTD WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP