



SHELL SIZE	A THREAD	B MAX	C MAX	D MAX	E MAX	F MAX
03	9/16 -24UNEF	17,0	17,0	25,3	26,6	28,4
08	1/2 -20UNF	15,6	16,8	25,1	24,7	27,8
10	5/8 -24UNEF	18,6	17,0	25,9	26,7	29,5
12	3/4 -20UNEF	21,7	17,5	26,3	29,2	31,0
14	7/8 -20UNEF	24,9	18,3	26,6	30,7	32,6
16	1 -20UNEF	28,2	19,2	27,4	34,2	34,2
18	1 1/16 -18UNEF	30,9	19,4	28,2	37,2	34,9
20	1 3/16 -18UNEF	34,1	20,3	28,5	42,2	36,5
22	1 5/16 -18UNEF	37,3	20,5	29,3	44,2	38,1
24	1 7/16 -18UNEF	40,4	22,0	29,7	45,2	39,6
28	1 3/4 -18UNS	50,0	23,5	30,7	54,4	44,3
32	2 -18UNS	56,3	25,2	32,4	60,9	47,4
36	2 1/4 -16UN	62,7	26,4	33,6	67,4	50,8
40	2 1/2 -16UN	69,0	28,8	34,8	73,4	53,8
44	2 3/4 -16UN	75,4	30,3	36,5	79,7	57,0
48	3 -16UN	81,7	31,5	37,7	86,0	60,1
61	1 1/2 -18UNEF	42,0	22,3	30,1	48,0	41,1

ENTRY SIZE	G	H LENGTH	J LENGTH	CABLE DIA RANGE
05	7,92	60	40	4,5 - 9,0
08	12,70	60	40	6,0 - 12,0
10	15,88	72	48	7,5 - 15,0
12	19,05	72	48	9,0 - 18,0
16	25,40	95	55	10,0 - 25,0
20	31,80	125	70	12,5 - 25,0
24	38,10	125	70	15,0 - 36,0

TAKA1-16-08-1-C-UB

SERIES \_\_\_\_\_

CONNECTOR INTERFACE \_\_\_\_\_

ANGLE \_\_\_\_\_

SHELL SIZE \_\_\_\_\_

ENTRY SIZE \_\_\_\_\_

MATERIAL \_\_\_\_\_

PLATING \_\_\_\_\_

HEAT SHRINK TERMINATION; UB - UNSCREENED BOOT  
SB - SCREENED BOOT

HEAT SHRINK ADAPTOR	SERIES TAK TO FIT CONNECTOR CODE A	
	THIS DRAWING IS THE COPYRIGHT AND THE PROPERTY OF POLAMCO LTD. IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT WRITTEN CONSENT OF THE COMPANY	
	POLAMCO LTD	WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP