



SHELL SIZE	A THREAD	B MAX	C MAX	D MAX	E MAX	F MAX
08	$\frac{7}{16}$ -28UNEF	17,3	14,1	24,8	25,2	28,4
10	$\frac{9}{16}$ -24UNEF	20,3	14,9	25,5	28,2	30,2
12	$\frac{11}{16}$ -24UNEF	23,8	15,3	26,1	31,7	31,7
14	$\frac{13}{16}$ -20UNEF	26,8	16,2	26,7	35,2	33,2
16	$\frac{15}{16}$ -20UNEF	29,8	16,5	27,5	38,2	34,9
18	$1\frac{1}{16}$ -18UNEF	33,3	17,3	28,5	41,7	36,5
20	$1\frac{3}{16}$ -18UNEF	36,3	18,2	28,8	45,2	38,1
22	$1\frac{5}{16}$ -18UNEF	39,8	18,5	29,1	48,2	39,6
24	$1\frac{7}{16}$ -18UNEF	42,8	19,4	30,0	51,2	41,1

ENTRY SIZE	G	H LENGTH	J LENGTH	CABLE DIA RANGE
05	7,92	60	40	4,5 - 9,0
08	12,70	60	40	6,0 - 12,0
10	15,88	72	48	7,5 - 15,0
12	19,05	72	48	9,0 - 18,0
16	25,40	95	55	10,0 - 25,0
20	31,80	125	70	12,5 - 25,0
24	38,10	125	70	15,0 - 36,0

TAKD1-16-08-1-C-UB

SERIES \_\_\_\_\_  
CONNECTOR INTERFACE \_\_\_\_\_  
ANGLE \_\_\_\_\_  
SHELL SIZE \_\_\_\_\_  
ENTRY SIZE \_\_\_\_\_  
MATERIAL \_\_\_\_\_  
PLATING \_\_\_\_\_  
HEAT SHRINK TERMINATION; UB - UNSCREENED BOOT  
SB - SCREENED BOOT

HEAT SHRINK ADAPTOR	<b>SERIES TAK</b> TO FIT CONNECTOR CODE D
	THIS DRAWING IS THE COPYRIGHT AND THE PROPERTY OF POLAMCO LTD. IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT WRITTEN CONSENT OF THE COMPANY
<b>POLAMCO LTD</b>	WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP