



SHELL SIZE	A THREAD	B MAX	C MAX	D MAX	E MAX	F MAX
08	7/16 -28UNEF	18,0	18,7	25,3	23,1	28,4
10	1/2 -28UNEF	19,5	20,0	26,0	24,6	29,3
11	9/16 -24UNEF	21,0	19,3	26,1	26,6	30,2
12	5/8 -24UNEF	23,0	19,8	26,3	28,1	31,0
14	3/4 -20UNEF	26,0	20,7	26,9	32,6	33,2
16	7/8 -20UNEF	30,5	21,4	28,2	36,1	34,9
18	1 20UNEF	34,0	22,0	28,5	39,1	36,5
20	1 1/8 -18UNEF	37,0	22,7	29,3	42,6	38,1
22	1 1/4 -18UNEF	40,0	23,3	29,7	45,6	39,6
24	1 3/8 -18UNEF	43,5	23,9	30,1	48,6	41,1
28	1 5/8 -18UNEF	50,0	25,0	30,1	53,6	43,6
32	1 7/8 -16UN	56,0	27,7	35,2	60,0	46,8
36	2 1/8 -16UN	64,0	29,0	33,7	69,6	51,6
40	2 3/8 -16UN	68,5	31,5	34,8	74,1	53,8

ENTRY SIZE	G	H LENGTH	J LENGTH	CABLE DIA RANGE
05	7,92	60	40	4,5 - 9,0
08	12,70	60	40	6,0 - 12,0
10	15,88	72	48	7,5 - 15,0
12	19,05	72	48	9,0 - 18,0
16	25,40	95	55	10,0 - 25,0
20	31,80	125	70	12,5 - 25,0
24	38,10	125	70	15,0 - 36,0

TAKLC1-16-08-1-C-UB

SERIES _____

CONNECTOR INTERFACE _____

ANGLE _____

SHELL SIZE _____

ENTRY SIZE _____

MATERIAL _____

PLATING _____

HEAT SHRINK TERMINATION; UB - UNSCREENED BOOT
SB - SCREENED BOOT

HEAT SHRINK ADAPTOR	SERIES TAK TO FIT CONNECTOR CODE LC	
	THIS DRAWING IS THE COPYRIGHT AND THE PROPERTY OF POLAMCO LTD. IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT WRITTEN CONSENT OF THE COMPANY	
	POLAMCO LTD	WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP