



SHELL SIZE	A THREAD	B MAX	C MAX	D MAX	E MAX	F MAX
12	5/8 -24UNEF	20,3	15,7	30,1	25,2	29,3
14	3/4 -20UNEF	23,7	16,7	30,7	29,2	30,2
16	7/8 -20UNEF	26,7	24,4	31,2	32,2	31,8
18	1 -20UNEF	30,3	25,1	31,6	35,2	33,3
20	1 1/8 -18UNEF	35,3	25,6	32,3	38,2	36,5
22	1 1/4 -18UNEF	38,3	26,4	33,0	41,2	36,5
24	1 3/8 -18UNEF	41,3	27,6	33,6	44,2	38,2
28	1 5/8 -18UNEF	47,8	29,3	34,8	51,3	40,3
32	1 7/8 -16UN	54,2	30,2	36,1	58,2	44,5
36	2 1/16 -16UNS	62,2	31,7	36,9	63,2	47,2

ENTRY SIZE	G	H LENGTH	J LENGTH	CABLE DIA RANGE
05	7,92	60	40	4,5 - 9,0
08	12,70	60	40	6,0 - 12,0
10	15,88	72	48	7,5 - 15,0
12	19,05	72	48	9,0 - 18,0
16	25,40	95	55	10,0 - 25,0
20	31,80	125	70	12,5 - 25,0
24	38,10	125	70	15,0 - 36,0

TAKQ1-16-08-1-C-UB

SERIES \_\_\_\_\_  
CONNECTOR INTERFACE \_\_\_\_\_  
ANGLE \_\_\_\_\_  
SHELL SIZE \_\_\_\_\_  
ENTRY SIZE \_\_\_\_\_  
MATERIAL \_\_\_\_\_  
PLATING \_\_\_\_\_  
HEAT SHRINK TERMINATION; UB - UNSCREENED BOOT  
SB - SCREENED BOOT

NOTE:  
FOR ENVIRONMENTAL SEALING  
PLEASE USE GROMMET ABB-\*\*\*-GAC  
(SUPPLIED BY AB CONNECTORS)

HEAT SHRINK ADAPTOR	SERIES TAK TO FIT CONNECTOR CODE Q	
	THIS DRAWING IS THE COPYRIGHT AND THE PROPERTY OF POLAMCO LTD. IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT WRITTEN CONSENT OF THE COMPANY	
	POLAMCO LTD	WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP