



SHELL SIZE	A THREAD	B MAX	C MAX	D MAX	E MAX	F MAX
12	5/8 -24UNEF	21,7	14,7	25,4	22,2	28,2
14	3/4 -20UNEF	24,8	15,3	26,3	25,4	29,7
16	7/8 -20UNEF	28,8	16,0	26,2	28,6	31,2
18	1 -20UNEF	32,0	16,7	26,6	30,1	33,2
20	1 1/8 -18UNEF	35,0	17,7	28,3	33,2	35,7
22	1 1/4 -18UNEF	38,3	18,1	28,6	38,0	34,7
24	1 3/8 -18UNEF	41,5	18,6	29,7	39,6	36,7
28	1 5/8 -18UNEF	48,0	20,1	30,2	41,4	43,7
32	1 7/8 -16UNEF	54,5	21,1	31,2	41,4	46,2

ENTRY SIZE	G	H LENGTH	J LENGTH	CABLE DIA RANGE
05	7,92	60	40	4,5 - 9,0
08	12,70	60	40	6,0 - 12,0
10	15,88	72	48	7,5 - 15,0
12	19,05	72	48	9,0 - 18,0
16	25,40	95	55	10,0 - 25,0
20	31,80	125	70	12,5 - 25,0
24	38,10	125	70	15,0 - 36,0

TAKR1-18-08-1-C-UB

SERIES _____
CONNECTOR INTERFACE _____
ANGLE _____
SHELL SIZE _____
ENTRY SIZE _____
MATERIAL _____
PLATING _____
HEAT SHRINK TERMINATION; UB - UNSCREENED BOOT
SB - SCREENED BOOT

NOTE:
FOR ENVIRONMENTAL SEALING
PLEASE USE GROMMET SB-**-**-G
(SUPPLIED BY AB CONNECTORS)

HEAT SHRINK ADAPTOR	SERIES TAK TO FIT CONNECTOR CODE R	
	THIS DRAWING IS THE COPYRIGHT AND THE PROPERTY OF POLAMCO LTD. IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT WRITTEN CONSENT OF THE COMPANY	
 POLAMCO LTD	WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP	