


SHELL SIZE	A THREAD	B MAX	C MAX	D MAX	E MAX	F MAX
08	$\frac{7}{16}$ -28UNEF	19,3	16,1	24,8	27,5	30,1
10	$\frac{9}{16}$ -24UNEF	21,3	16,9	25,5	31,0	31,5
12	$\frac{11}{16}$ -24UNEF	24,3	17,3	26,1	34,0	32,8
14	$\frac{13}{16}$ -20UNEF	29,2	18,2	26,7	37,0	34,5
16	$\frac{15}{16}$ -20UNEF	30,8	18,5	27,5	40,4	36,3
18	$1\frac{1}{16}$ -18UNEF	33,8	19,3	28,5	43,6	37,7
20	$1\frac{3}{16}$ -18UNEF	38,5	20,1	28,8	46,8	38,9
22	$1\frac{5}{16}$ -18UNEF	38,5	20,6	29,2	49,8	40,0
24	$1\frac{7}{16}$ -18UNEF	42,5	21,4	30,0	52,8	41,9

ENTRY SIZE	G	H LENGTH	J LENGTH	CABLE DIA RANGE
05	7,92	60	40	4,5 - 9,0
08	12,70	60	40	6,0 - 12,0
10	15,88	72	48	7,5 - 15,0
12	19,05	72	48	9,0 - 18,0
16	25,40	95	55	10,0 - 25,0
20	31,80	125	70	12,5 - 30,0
24	38,10	125	70	15,0 - 36,0

TAKS1-16-08-2-Z-UB

SERIES _____
 CONNECTOR INTERFACE _____
 ANGLE _____
 SHELL SIZE _____
 ENTRY SIZE _____
 MATERIAL _____
 PLATING _____
 HEAT SHRINK TERMINATION; UB - UNSCREENED BOOT
 SB - SCREENED BOOT

HEAT SHRINK ADAPTOR	SERIES TAK TO FIT CONNECTOR CODE S	
	THIS DRAWING IS THE COPYRIGHT AND THE PROPERTY OF POLAMCO LTD. IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT WRITTEN CONSENT OF THE COMPANY	
	POLAMCO LTD	WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP