



SHELL SIZE	A THREAD	B MAX	C MAX	D MAX	E MAX	F MAX
11	$\frac{3}{4}$ -24UNEF	26,5	20,2	25,6	31,7	30,2
13	$\frac{7}{8}$ -20UNEF	29,7	21,3	26,5	34,8	31,7
15	1-20UNEF	31,3	21,7	26,8	37,2	33,2
17	$1\frac{1}{8}$ -18UNEF	35,5	21,7	27,9	40,0	34,3
19	$1\frac{1}{4}$ -18UNEF	38,7	22,5	33,2	43,3	36,0
23	$1\frac{7}{16}$ -18UNEF	43,6	23,1	35,0	48,7	39,0
25	$1\frac{9}{16}$ -18UNEF	47,2	24,1	35,5	51,5	40,1
29	$1\frac{7}{8}$ -16UN	55,2	26,2	35,2	58,5	43,2
33	$2\frac{1}{16}$ -16UN	60,5	27,2	35,2	63,4	45,7

ENTRY SIZE	G	H LENGTH	J LENGTH	CABLE DIA RANGE
05	7,92	60	40	4,5 - 9,0
08	12,70	60	40	6,0 - 12,0
10	15,88	72	48	7,5 - 15,0
12	19,05	72	48	9,0 - 18,0
16	25,40	95	55	10,0 - 25,0
20	31,80	125	70	12,5 - 25,0
24	38,10	125	70	15,0 - 36,0

TAKZ1-17-08-1-C-UB

SERIES _____
CONNECTOR INTERFACE _____
ANGLE _____
SHELL SIZE _____
ENTRY SIZE _____
MATERIAL _____
PLATING _____
HEAT SHRINK TERMINATION; UB - UNSCREENED BOOT
SB - SCREENED BOOT

HEAT SHRINK ADAPTOR	SERIES TAK TO FIT CONNECTOR CODE Z	
	THIS DRAWING IS THE COPYRIGHT AND THE PROPERTY OF POLAMCO LTD. IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT WRITTEN CONSENT OF THE COMPANY	
	POLAMCO LTD	WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP